

4-20 mA output , Measure range 0 ~ 50000 lux

# LIGHT TRANSMITTER

Model : TRLX-101

*ISO-9001, CE, IEC1010*



**Lutron**



**LUTRON ELECTRONIC**

*The Art of Measurement*

4-20 mA output , Measure range 0 ~ 50000 lux

# LIGHT TRANSMITTER

Model : TRLX-101

## FEATURES

* 4-wire installation.
* Linear current output .
* Easy installation and connection.
* Measure range 0 to 50000 lux.
* Zero & Span adjustment VR.
* Separate Light sensor probe easy operation.

## Electrical Specifications (23±5 °C)

### Light

Unit	lux	mA Output	Resolution
Range 1	0 to 2000 Lux	4.00~ 20.00 mA	0.006 mA / 1Lux
Range 2	0 to 20000 Lux	4.00~ 20.00 mA	0.006 mA / 10Lux
Range 3	0 to 50000 Lux	4.00~ 8.00 mA	0.008 mA / 100Lux
Accuracy	±( 5 % + 2 d ) reading		

## Electrical Specification

Measurement	LIGHT
Analog output	Analog output: 4 to 20 mA. * <i>linear to temperature.</i>
Loop impedance	Max. 200 Ω@24 V DC.
Power supply	Isolated Power 9 to 30VDC@200 mA. * <i>Ripple &lt; 2.5%</i>
Operation Temp.	0°C to 70°C /32°F to 158°F.
Operation humidity	Max. 85% RH.
Dimensions	120 mm x 96 mm x 43 mm.
Weight	164 g.
Enclosure rating	IP63
Dimension	<i>Meter :</i> 182 x 73 x 47.5 mm <i>Light sensor probe:</i> Round 16 mm Dia. x 37 mm. Cable length : 1.2 meter.
Accessories Included	* Instruction manual..... 1 PC  * Light sensor probe..... 1 PC